

**Amendments to the Claims:**

1. **(Original)** A suspension comprising:  
a plurality of roll sections each of which has a semicylindrical shape in a cross section,  
wherein the roll sections are disposed side by side based on a straight line connecting two points on an inner periphery or an outer periphery,  
wherein the roll sections form a closed loop in a manner that a roll section of the roll sections being disposed first adjoins a roll section of the roll sections being disposed last,  
wherein adjacent roll sections are coupled with each other through a boundary section forming a continuous three dimensional curved surface.
  
2. **(Original)** A suspension comprising:  
a plurality of roll sections each of which has a semicylindrical shape in a cross section,  
wherein the roll sections are disposed radially side by side at regular intervals based on a straight line connecting two points on an inner periphery or an outer periphery,  
wherein the roll sections form a closed loop in a manner that a roll section of the roll sections being disposed first adjoins a roll section of the roll sections being disposed last,  
wherein adjacent roll sections are coupled with each other through a boundary section forming a continuous three dimensional curved surface.
  
3. **(Currently amended)** The suspension of claim 1 ~~or 2~~,  
wherein the inner periphery is coupled with the roll sections forming the closed loop, and non-continuous parts of the inner periphery are trimmed,  
wherein the outer periphery has a frame fixing part for being fixed at a frame.
  
4. **(Currently amended)** The suspension of claim 1 ~~or 2~~,

wherein the outer periphery is coupled with the roll sections forming the closed loop, and non-continuous parts of the outer periphery are trimmed,

wherein the inner periphery has a vibration system fixing part for fixing a diaphragm or a voice coil.

5. **(Currently amended)** The suspension of claim 1 ~~or 2~~,  
wherein an odd number of the roll sections are disposed.

6. **(Currently amended)** A suspension device comprising:  
two suspensions of claim 1 ~~or 2~~ being disposed in a substantially vertical direction.

7. **(Currently amended)** A suspension device comprising:  
two suspensions of claim 1 ~~or 2~~ being disposed in a substantially vertical direction,  
wherein one of the suspensions is rotated by 1/2 of a width of the roll section with respect to an axis in a periphery direction.

8. **(Currently amended)** An electro-acoustic transducer comprising:  
a suspension of claim 1 ~~or 2~~,  
wherein the inner periphery is coupled with a voice coil placed in a magnetic gap of a magnetic circuit or an outer periphery part of a diaphragm coupled with the voice coil,  
wherein the outer periphery is fixed to a frame which supports the magnetic circuit and a vibration system.

9. **(New)** The suspension of claim 2,  
wherein the inner periphery is coupled with the roll sections forming the closed loop, and non-continuous parts of the inner periphery are trimmed,  
wherein the outer periphery has a frame fixing part for being fixed at a frame.

10. **(New)** The suspension of claim 2,  
wherein the outer periphery is coupled with the roll sections forming the closed loop, and  
non-continuous parts of the outer periphery are trimmed,  
wherein the inner periphery has a vibration system fixing part for fixing a diaphragm or a  
voice coil.

11. **(New)** The suspension of claim 2,  
wherein an odd number of the roll sections are disposed.

12. **(New)** A suspension device comprising:  
two suspensions of claim 2 being disposed in a substantially vertical direction.

13. **(New)** A suspension device comprising:  
two suspensions of claim 2 being disposed in a substantially vertical direction,  
wherein one of the suspensions is rotated by  $1/2$  of a width of the roll section with respect  
to an axis in a periphery direction.

14. **(New)** An electro-acoustic transducer comprising:  
a suspension of claim 2,  
wherein the inner periphery is coupled with a voice coil placed in a magnetic gap of a  
magnetic circuit or an outer periphery part of a diaphragm coupled with the voice coil,  
wherein the outer periphery is fixed to a frame which supports the magnetic circuit and a  
vibration system.